



ADVANTAGES

- Adjustable room side diffusion disc
- Gel seal between filter and housing
- Noise reducing rounded collar
- Welded housing
- Low Profile
- Room side replaceable HEPA filter module
- Housing can be installed from room and top side
- Gap free, architecturally pleasing room side surface

Application	Microelectronic, Hospitals, Life science
Frame	Anodized aluminium
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Max Temperature (°C)	93° C
Comment	DOP efficiency: ≥ 99.99 Fire rating: UL 900 Housing Frame: Extruded aluminium Back plate: Hot dipped galvanized steel

Art. No.	Type	EN1822	Dimensions WxHxD (mm)	Filter size HxWxD (mm)	Con. Ø (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
15290001	Slimline RSR - 600*600	H13		600x600		4.5/121	4.7
15290002	Slimline RSR - 905*600	H13		600x905		680/120	6.6
15290003	Slimline RSR - 1210*600	H13		600x1210		947/119	7.9
4109001	SLM Housing 600*600* Ø250		600x600x133		250		9.72
4109002	SLM Housing 905*600* Ø305		905x600x133		305		9.8
4109003	SLM Housing 1210*600* Ø305		1210x600x133		305		9.91

*Other dimensions, finishes and different options are available on request